

UNCLASSIFIED

AD NUMBER

AD208580

CLASSIFICATION CHANGES

TO: unclassified

FROM: confidential

LIMITATION CHANGES

TO:

Approved for public release, distribution
unlimited

FROM:

Distribution authorized to U.S. Gov't.
agencies and their contractors;
Administrative/Operational Use; 27 Jul
1953. Other requests shall be referred to
U.S. Naval Ordnance Lab., White Oak, MD.

AUTHORITY

19 Jan 1959, NOL ltr; NOC ltr, 9 Jun 1966

THIS PAGE IS UNCLASSIFIED

UNCLASSIFIED

A208580

Armed Services Technical Information Agency

**ARLINGTON HALL STATION
ARLINGTON 12 VIRGINIA**

BEST AVAILABLE COPY

**FOR
MICRO-CARD
CONTROL ONLY**

1 OF 1

NOTICE: WHEN GOVERNMENT OR OTHER DRAWINGS, SPECIFICATIONS OR OTHER DATA ARE USED FOR ANY PURPOSE OTHER THAN IN CONNECTION WITH A DEFINITELY RELATED GOVERNMENT PROCUREMENT OPERATION, THE U. S. GOVERNMENT THEREBY INCURS NO RESPONSIBILITY, NOR ANY OBLIGATION WHATSOEVER; AND THE FACT THAT THE GOVERNMENT MAY HAVE FORMULATED, FURNISHED, OR IN ANY WAY SUPPLIED THE SAID DRAWINGS, SPECIFICATIONS, OR OTHER DATA IS NOT TO BE REGARDED BY IMPLICATION OR OTHERWISE AS IN ANY MANNER LICENSING THE HOLDER OR ANY OTHER PERSON OR CORPORATION, OR CONVEYING ANY RIGHTS OR PERMISSION TO MANUFACTURE, USE OR SELL ANY PATENTED INVENTION THAT MAY IN ANY WAY BE RELATED THERETO.

UNCLASSIFIED

UNCLASSIFIED

NAVORD REPORT

2890

AIR BLAST RESULTING FROM THE DETONATION
OF SMALL TNT CHARGES

FILE COPY

Return to

ASTIA

ARLINGTON HALL STATION

ARLINGTON 12, VIRGINIA

Attn: TISSS

27 JULY 1953

FILE COPY

Return to

ASTIA

ARLINGTON HALL STATION

ARLINGTON 12, VIRGINIA

Attn: TISSS

Classification cancelled
or changed to Unclassified

AUTH: NOA ltr, 14 Jan 59

By Charles C. Beck

Signature and Grade

Date 19 Jan 59



U. S. NAVAL ORDNANCE LABORATORY
WHITE OAK, MARYLAND

SECURITY INFORMATION

UNCLASSIFIED

DEC 12 1957

5744 43724

This document contains information affecting the national defense of the United States within the meaning of the Espionage Act, 50 USC, 31 and 32, as amended. Its transmission or the revelation of its contents, in any manner to an unauthorized person, is prohibited by law.

Reproduction of this matter in any form by other than naval activities is not authorized except by specific approval of the Secretary of the Navy.

UNCLASSIFIED

~~CONFIDENTIAL~~
NAVORD Report 2890

AIR BLAST RESULTING FROM THE DETONATION
OF SMALL TNT CHARGES

By

E. M. Fisher
J. F. Pittman

Approved by: J. F. Moulton, Jr.
Acting Chief,
Explosion Effects Division

↓
ABSTRACT: Centrally boosting one pound cast TNT spheres resulted in obtaining air blast peak pressures about 15 per cent below the accepted values. Placing the booster half in and half out of the surface of a one pound cast TNT sphere resulted in a detonation that produced the accepted peak air blast pressures. A larger 7.9 pound spherical cast TNT charge was fired to show that the accepted values of blast could be obtained by central initiation providing the charge was large enough.

It was noted that the secondary shock was in a decidedly different location for a poor detonating charge as compared to charges yielding the accepted values of peak pressure.

The effect of poor detonation on impulse was about half as much as it was for peak pressure.

Explosives Research Department
U.S. NAVAL ORDNANCE LABORATORY
White Oak, Maryland

1

~~CONFIDENTIAL~~
SECURITY INFORMATION

UNCLASSIFIED

DL
57AA45784

UNCLASSIFIED

NAVORD Report 2890

27 July 1953

The work described in this report was done in order to demonstrate the difficulty of detonating small charges of TNT and to warn those using small charge TNT data of the possible pitfalls of poor detonation. This work describes a number of ways of recognizing poor detonation in TNT and a successful way for boosting a one-pound spherical TNT charge. This work was performed under Task NOL-Re2c-2-1-53.

The authors wish to acknowledge the work of the investigation group who aided in the field and data reduction work:

J. D. Rowe
R. Robertson
E. Murray
M. J. Bengston
R. Huff

EDWARD L. WOODYARD
Captain, USN
Commander


PAUL M. FYE
By direction

UNCLASSIFIED

UNCLASSIFIED

~~CONFIDENTIAL~~
NAVORD Report 2890

CONTENTS

	Page
Introduction	1
Design of Experiment	1
Analysis of the Data	2
Conclusions	3
References	7

ILLUSTRATIONS

Figure 1. Plan of Gage and Charge Layout	8
Figure 2. Peak Pressure vs Reduced Distance	9
Figure 3. Reduced Positive Impulse vs Reduced Distance	10
Figure 4. Time to Secondary Shock vs Charge Distance	11
Figure 5. Typical Records	12
Table I Peak Pressure Results	5
Table II Positive Impulse Results	6

UNCLASSIFIED

~~CONFIDENTIAL~~
NAVORD Report 2890

AIR BLAST RESULTING FROM THE DETONATION OF SMALL TNT CHARGES

INTRODUCTION

1. Experimental work has in the past indicated that TNT is a fairly troublesome explosive to detonate high order. Unpublished work recalled by people from the Underwater Explosive Research Laboratory, UERL, indicates that cylindrical TNT charges in small weights (under one pound) very often detonated poorly both in air and underwater. Unpublished experimental work at UERL further indicated that the best way to detonate a cylindrical charge is to use a booster located half in and half out of one of the ends as contrasted with a booster centrally located or a booster completely outside the charge on one end.
2. The experience of the air blast group at the Naval Ordnance Laboratory in the recent past has indicated that a one pound spherical charge of TNT centrally detonated by a 45 gram spherical pentolite booster gave a peak pressure blast effect that would be expected by three-fourths of a pound of TNT and a positive impulse blast effect of nine-tenths of a pound of TNT. Poor detonation was suspected as the cause of this effect. This report will discuss the experiment designed to determine whether poor detonation was the cause of this effect and if so how to detonate properly one pound of spherically cast TNT. This experiment will also show that the scaling laws for peak pressure for one and eight pounds of TNT apply when detonation is proper.

DESIGN OF EXPERIMENT

3. Six 7.9 pound charges of cast spherical TNT centrally initiated with a 0.5 pound spherical pentolite booster were fired as the control shots since it was known that these charges detonate properly (reference (a)). Six one pound spherical charges of cast TNT centrally initiated with a 45 gram spherical pentolite booster were fired in order to repeat the poor performance of these charges that was previously observed. Six one pound spherical cast TNT charges were fired in which the 45 gram spherical pentolite booster was located half in and half out of the surface of the sphere of TNT. This was an attempt to get successful detonation of a sphere by techniques described for cylinders. When mounted for firing, these charges

UNCLASSIFIED

~~CONFIDENTIAL~~
NAVORD Report 2890

were oriented with the booster vertically above the charge center.

4. All of the above charges were fired with an Engineer Special detonator. Charges and gages were placed on a horizontal plane 12 feet in the air. A plan view of the set-up is shown in Fig. 1. Measurements of peak pressure were made by the velocity method (reference (b)), using the two-cap method for wind and sound velocity measurements. Pressure-time measurements were made by tourmaline piezo-electric gages using conventional techniques, (reference (c)). Briefly these techniques involve the use of cables leading the tourmaline piezo-electric gage signals back to the recording system. The recording system amplifies these signals and impresses them on the deflection plates of a cathode ray tube. The resulting deflection of the cathode ray spot is photographed as a function of time by a rotating drum camera.

ANALYSIS OF THE DATA

5. Peak pressure was calculated by the application of the peak pressure-shock velocity relation derived from the Rankine-Hugoniot equations, references (b) and (c). Positive impulse was calculated by integrating under the positive phase of the pressure-time curve including that portion of the secondary shock, Fig. 5, that is in the positive phase. The pressure scale for the pressure-time records was determined from the pressure as measured by the velocity method for the particular shot and distance rather than by a gage calibration. Allowance was made for the effect of finite gage size in reducing the apparent peak height in the pressure-time records.

6. In Fig. 2 graphs of peak pressure versus reduced distance show clearly the poor results obtained by central initiation of one pound bare spherical charges of cast TNT in comparison to similar charges detonated with boosters half in and half out of the spherical surface. Fig. 2 shows also that central initiation for the 7.9 pound sphere of TNT produces air blast peak pressures that scale to those obtained for the surface initiation of the one pound spheres and also that the slope of the pressure distance curves for surface initiation of the spherical charge is essentially the same as for central initiation. These results are in agreement with previous 7.9 pound results, reference (a), which are in turn the accepted values at sea level for TNT when detonation is considered high order.

2/
~~CONFIDENTIAL~~
SECURITY INFORMATION

UNCLASSIFIED

UNCLASSIFIED

~~CONFIDENTIAL~~
NAVORD Report 2890

7. Table I is a compilation of the experimental peak pressure results and Table II is a compilation of the experimental positive impulse values obtained from all shots in these tests.

8. The table below expresses the results of these experiments in terms of the ratio of the weight of TNT detonating in the accepted manner to the weight of TNT in the test charge that will produce the same blast effect at the same distance.

Charge Description	:Peak Pres- :sure Results	:Positive Im- :pulse Results
7.9 pound Spherical Cast TNT with central 0.5 lb spheri- cal pentolite booster	: : : : 1.00	: : : : -
One pound Spherical Cast TNT with 45 gram spherical pento- lite booster embedded half in: and half out of spherical surface	: : : : 1.01 \pm .03* :	: : : : 1.00 :
One pound Spherical Cast TNT with central 45 gram spheri- cal pentolite booster	: : : : 0.81 \pm .02 :	: : : : 0.91 :

*Standard error.

9. Examination of the pressure-time records, Fig. 5, reveals an interesting effect on the secondary shock. For the two types of charges producing the accepted blast parameters for TNT the secondary shock stayed close to the atmospheric pressure level. For the charge producing blast less than the accepted TNT values the secondary shock occurred decidedly earlier in time with respect to the primary shock. Fig. 4 shows graphically the time difference between primary and secondary shock as a function of distance for the two kinds of one pound TNT charges fired.

CONCLUSIONS

10. TNT can give erroneous air blast results when initiation is not proper. These erroneous results can

CONFIDENTIAL
NAVORD Report 2890

be obtained as consistently as the accepted results. In these experiments central initiation of one pound of TNT produced peak pressures about 15 per cent lower than surface initiation of the same one pound spheres of TNT.

11. The location of the secondary shock on the time base relative to the primary shock may yield information as to the quality of the detonation. Proper detonation in TNT in these experiments placed the secondary shock furthest away in time from the primary shock, see Fig. 5. The slope of the pressure-distance curve for the surface initiation of the spherical charge compared to the centrally initiated charge, appears to be the same in the region measured.

12. The effect of the poor detonation on positive impulse was about half as much as it was for peak pressure.

CONFIDENTIAL
NAVORD Report 2890

TABLE I

PEAK PRESSURE RESULTS

1# Cast TNT Sphere with Booster Centrally Located

SHOT	d	5.70	6.70	7.70	8.95	10.70	12.95	16.20	20.70
	r	5.71	6.71	7.71	8.96	10.71	12.96	16.22	20.72
1		17.09	11.35	10.67	7.34	5.46	4.12	2.74	1.49
3		18.58	14.25	10.66	8.89	6.07	3.80	2.62	1.80
4		17.63	14.43	10.15	8.14	5.13	3.87	2.39	1.39
6		19.17	13.92	10.36	7.85	6.20	4.36	3.27	2.18
9		18.42	12.65	11.09	7.99	6.07	4.29	3.18	2.37
11		17.86	12.10	10.06	6.65	4.95	3.45	2.32	1.47
13		18.22	11.96	10.45	6.79	5.28	3.67	2.53	1.53
Mean		18.14	12.95	10.49	7.66	5.59	3.94	2.72	1.75
σ		3.8%	9.6%	3.4%	10.4%	9.1%	8.5%	13.6%	22.0%
σ_p		1.4%	3.6%	1.3%	3.9%	3.5%	3.2%	5.1%	8.3%

$$P = -.637 + \frac{33.546}{r} + \frac{286.411}{r^2} + \frac{755.234}{r^3}$$

1# Cast TNT Spheres with Booster half in and half out of Spherical Surface

SHOT	d	5.70	6.70	7.70	8.95	10.70	12.95	16.20	20.70
	r	5.64	6.63	7.62	8.86	10.59	12.82	16.04	20.49
2		22.40	15.65	12.37	9.55	6.40	5.05	3.46	2.22
5		21.59	15.81	13.59	9.50	6.73	4.79	3.21	1.90
7		22.95	15.80	12.47	8.90	6.62	4.96	3.26	2.39
8		22.18	15.45	11.82	8.32	6.28	4.57	2.92	2.09
10		20.23	12.86	11.44	8.40	5.66	3.92	2.62	1.58
12		19.33	14.89	12.60	8.51	6.59	4.88	3.34	2.44
14		22.48	15.34	13.01	8.27	6.43	4.77	3.50	2.54
Mean		21.59	15.49	12.47	8.78	6.51	4.84	3.28	2.17
σ		6.1%	2.3%	5.7%	6.2%	2.5%	3.5%	6.4%	15.7%
σ_p		2.3%	0.9%	2.2%	2.4%	1.0%	1.4%	2.6%	5.9%

$$P = .086 + \frac{19.242}{r} + \frac{467.028}{r^2} + \frac{607.691}{r^3}$$

.9# Spherical Cast TNT with Centrally Located Booster

SHOT	d	7.70	8.95	10.70	12.95	16.20	20.70
	r	7.87	8.50	9.38	10.51	11.14	10.41
15		54.74	36.88	23.24	16.51	10.32	6.57
16		51.86	36.50	24.92	16.65	10.38	6.54
17		50.55	35.11	22.50	15.95	10.14	6.25
18			35.73	26.10	16.38	10.12	6.54
19			39.50	24.48	17.12		
20			36.48	23.98	15.81	10.18	6.34
Mean		52.39	36.14	24.20	16.40	10.23	6.45
σ		4.1%	2.0%	5.2%	2.9%	1.2%	2.2%
σ_p		2.4%	0.9%	2.1%	1.2%	0.5%	1.0%

$$P = -6.539 + \frac{152.834}{r} - \frac{559.978}{r^2} - \frac{3204.774}{r^3}$$

* Datum disregarded in accordance with Chauvenet's Criterion.

d = distance from charge in feet

r = reduced distance $d/W^{1/3}$, $\left(\frac{\text{ft}}{\text{lb}}\right)^{1/3}$

Pressures are in psi

σ = standard deviation

σ_p = standard error.

CONFIDENTIAL
SECURITY INFORMATION

TABLE II
POSITIVE IMPULSE RESULTS

1/2 Cast TNT Spheres with Booster Centrally Located

SHOT	d	7.70	8.95	10.70	12.95
	r	7.71	8.96	10.71	12.96
1		6.93 6.57	5.70	5.39 4.87	4.10 4.08
3		8.69 7.36	7.12 5.93	5.24 4.80	3.90 4.22
4		7.72 7.85	6.74 5.59	4.79 4.06	3.29 3.39
6		7.00 6.87	6.72 6.30	5.97 5.06	4.51 4.59
9		7.82 6.74	6.35 6.26	6.31 5.41	4.38 4.59
11		8.12 6.34	6.50 5.17	4.14 3.91	3.57 3.70
13		7.39 6.87	5.72 5.18	4.81 4.02	3.83 3.76
Mean		7.26	6.10	4.91	3.99
$1/r^{1/3}$		7.27	6.11	4.91	3.99
$\% \sigma$		9.8%	10.0%	14.9%	10.8%
$\% \sigma_i$		2.6%	2.8%	4.1%	2.6%

1/2 Cast TNT Spheres with Booster
Half in and Half out of Spherical Surface

SHOT	d	7.70	8.95	10.70	12.95
	r	7.62	8.88	10.52	12.68
2		7.32	6.47	5.77 5.32	4.62
5		7.90 8.10	7.21 7.10	6.15 5.53	4.59 4.57
7		7.72 7.35	6.92 6.42	6.01 5.58	4.40 4.73
8		7.04 6.98	6.99 5.40	5.41 4.81	4.02 4.17
10		7.62 6.66	6.13 5.59	4.69 4.59	
12		8.74 8.23	7.04 6.49	6.16 5.20	4.39 4.19
14		9.42 7.25	7.41 7.02	5.47 5.31	4.06
Mean		7.58	6.63	5.42	4.40
$1/r^{1/3}$		7.50	6.56	5.37	4.36
$\% \sigma$		7.8%	9.4%	9.2%	5.6%
$\% \sigma_i$		2.1%	2.6%	2.4%	1.8%

7.5% Spherical Cast TNT with Centrally Located Booster

SHOT	d	7.70	8.95	10.70	12.95
	r	7.87	9.20	10.98	13.31
15		35.52 27.67	24.94 19.18	17.67	13.35 17.77
16		24.60 25.33	21.97 20.00	19.66 18.02	13.59 17.65
17		26.36 20.60	23.48 18.88	15.83	13.61 16.51
18			24.34 16.61	17.36 18.37	15.05 17.87
19				19.15 17.73	17.92 18.49
20		30.54 22.14	21.52 22.02	17.31 21.71	15.33 16.41
Mean		26.65	21.18	17.90	16.22
$1/r^{1/3}$		12.73	10.65	9.00	8.16
$\% \sigma$		13.2%	7.9%	5.1%	11.5%
$\% \sigma_i$		3.0%	3.4%	2.0%	3.3%

* Data disregarded in accordance with Chauvenet's Criterion.

d = distance from charge in feet
r = reduced distance $d/r^{1/3}$ (ft./lb.^{1/3})

Positive impulse is in pos.-m.

$1/r^{1/3}$ = reduced positive impulse

σ = standard deviation

σ_i = standard error.

CONFIDENTIAL
NAVORD Report 2890

REFERENCES

- a. E. M. Fisher, Spherical Cast TNT Charges, Air Blast Measurements on, NOLM-10780, Confidential, Jan 1950.
- b. P. Z. Kalavski, A High Speed Recording System Using the Velocity Method to Determine the Peak Pressure in Air by Explosives, NAVORD Report 2167, Unclassified, Feb 1952.
- c. G. K. Fraenkel, Apparatus for the Measurement of Air Blast Pressures by Means of Piezo-electric Gages, OSRD Report No. 6251, Unclassified, Mar 1946.

CONFIDENTIAL
NAVORD REPORT 2890




FIG. 1 PLAN OF GAGE AND CHARGE LAYOUT

CONFIDENTIAL
NAVORD REPORT 2890




FIG. 2 PEAK PRESSURE VS REDUCED DISTANCE

UNCLASSIFIED

NAVORD REPORT 2890




FIG. 3 REDUCED POSITIVE IMPULSE VS REDUCED DISTANCE

SECURITY
INFORMATION

10

UNCLASSIFIED

UNCLASSIFIED

~~CONFIDENTIAL~~

NAVORD REPORT 2890




FIG. 4 TIME TO SECONDARY SHOCK VS GAGE TO CHARGE DISTANCE


SECURITY
INFORMATION

UNCLASSIFIED

UNCLASSIFIED

~~CONFIDENTIAL~~
NAVORD REPORT 2890

A PORTION OF A VELOCITY RECORD




ARROWS SHOW PIPS PRODUCED BY GAGES ON ARRIVAL OF SOUND AND SHOCK WAVES. NUMBERS CORRESPOND TO VELOCITY GAGE NUMBERS OF FIG. 1, THIS REPORT

PRESSURE TIME RECORDS

1 LB CAST TNT SPHERE WITH
45 GRAM SPHERICAL PENTOLITE
BOOSTER LOCATED HALF
IN AND HALF OUT OF SPHERICAL
SURFACE



1 LB CAST TNT SPHERE WITH
45 GRAM SPHERICAL PENTOLITE
BOOSTER CENTRALLY LOCATED



PRIMARY SHOCK —
SECONDARY SHOCK —
GROUND REFLECTION —

THE ABOVE TWO RECORDS TAKEN AT THE SAME DISTANCE FROM THE TWO TYPES OF 1 LB CHARGES SHOW CLEARLY THE DIFFERENT LOCATIONS OF SECONDARY SHOCK

7.9 LB CAST TNT SPHERE WITH
1/2 LB SPHERICAL PENTOLITE
BOOSTER



NOTE: ALL TIMING MARKS
ARE AT 1 MILLISECOND
INTERVALS

FIG. 5

TYPICAL RECORDS

UNCLASSIFIED

~~CONFIDENTIAL~~
NAVORD Report 2890

DISTRIBUTION

	Copies
Chief, Bureau of Ordnance (Re2c)	5
Chief, Bureau of Aeronautics	2
Chief, Bureau of Medicine and Surgery	2
Chief, Bureau of Ships	2
Chief, Bureau of Yards and Docks	2
Chief of Naval Research, Code 466	1
Chief of Ordnance, Department of the Army, Washington, D.C.	2
Commanding General, Air Materiel Command, Wright Patterson Field, Air Force Base, Dayton, Ohio	2
Commander, Naval Ordnance Test Station, Inyokern, California Post Office - China Lake, California	3
Director, Ballistic Research Laboratories, Aberdeen Proving Ground, Maryland	2
Director, Naval Research Laboratory, Washington, D.C.	2
Chief, Armed Forces Special Weapons Project, Rm 1B684 The Pentagon, Washington, D.C.	2
Applied Physics Laboratory, Johns Hopkins University Silver Spring, Maryland via INM Silver Spring, Md.	1
Dr. E. F. Cox, Sandia Corporation, Sandia Base, Albuquerque, N. Mex., via INM, Los Angeles, Cal.	1
Miss Mary Lee Patterson, Librarian of Documents, Armour Research Foundation, Technology Center, Chicago 16, Illinois, via INM, Chicago, Illinois	1
Dr. E. B. Doll, Stanford Research Institute, Stanford, California, via Armed Forces Special Weapons Project, P.O.Box 2610, Pentagon Building, Washington, D.C.	1
Frank A. Parker, Director, Project Squid, Princeton University, Princeton, N.J. via INM, Newark, New Jersey	1
Director, Bureau of Mines, Washington, D.C., ATTN: Leonard A. Obert, Eastern Experiment Station	2

~~CONFIDENTIAL~~
SECURITY INFORMATION

UNCLASSIFIED

UNCLASSIFIED

~~CONFIDENTIAL~~
NAVORD Report 2890

DISTRIBUTION

	Copies
Office Chief of Ordnance, ORDTQ, Pentagon Bldg., ATTN: B. Drimmer	1
Commander, Naval Proving Ground, Dahlgren, Virginia	2
Los Alamos Scientific Laboratory, P.O.Box 1663, Los Alamos, N.M., via INM, Los Angeles, Calif.	1
University of Denver, via INM, Room 701, Buder Bldg., St. Louis, Missouri	1
Commanding Officer, Naval Mine Depot, Yorktown, Va. ATTN: J. Manley, R&D Division	1
Commanding Officer, Picatinny Arsenal, Dover, N. J.	1
Commanding General, Air Material Armament Test Center, Eglin Air Force Base, Florida	1
Hercules Experiment Station, Wilmington, Delaware ATTN: Dr. Roth, via INM, Philadelphia, Pa.	1
Bureau of Ordnance, Ad-8, for distribution as follows: British Joint Services Mission	5
Canadian Joint Staff for distribution	2
U. S. Naval Attache, London, England	1
Institute for Air Weapons Research, University of Chicago, Chicago Illinois, via Director, Office of Naval Research Branch Office, John Crerar Library Bldg - 10th Floor, 86 E. Randolph St., Chicago, Illinois	1
Denver Research Institute, University of Denver (Contract NORD 11541) Denver 10, Colorado via Asst. INM, Room 337, New Custom House, Denver, Colorado	1
National Fireworks Ordnance Co., West Hanover, Mass. (Contract NORD 11393) via INM, Springfield, Massachusetts	1

~~CONFIDENTIAL~~
SECURITY INFORMATION

UNCLASSIFIED

UNCLASSIFIED
A208580

Armed Services Technical Information Agency
ARLINGTON HALL STATION
ARLINGTON 12 VIRGINIA

FOR
MICRO-CARD
CONTROL ONLY

1 OF 1

NOTICE: WHEN GOVERNMENT OR OTHER DRAWINGS, SPECIFICATIONS OR OTHER DATA ARE USED FOR ANY PURPOSE OTHER THAN IN CONNECTION WITH A DEFINITELY RELATED GOVERNMENT PROCUREMENT OPERATION, THE U. S. GOVERNMENT THEREBY INCURS NO RESPONSIBILITY, NOR ANY OBLIGATION WHATSOEVER; AND THE FACT THAT THE GOVERNMENT MAY HAVE FORMULATED, FURNISHED, OR IN ANY WAY SUPPLIED THE SAID DRAWINGS, SPECIFICATIONS, OR OTHER DATA IS NOT TO BE REGARDED BY IMPLICATION OR OTHERWISE AS IN ANY MANNER LICENSING THE HOLDER OR ANY OTHER PERSON OR CORPORATION, OR CONVEYING ANY RIGHTS OR PERMISSION TO MANUFACTURE, USE OR SELL ANY PATENTED INVENTION THAT MAY IN ANY WAY BE RELATED THERETO.

UNCLASSIFIED